

# INSTARMAC

## SAFETY DATA SHEET ULTRASCAPE FLOWPOINT

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

<b>PRODUCT NAME</b>	ULTRASCAPE FLOWPOINT
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

### 2 HAZARDS IDENTIFICATION

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

**CLASSIFICATION (1999/45)** Xi;R37/38, R41. R43.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
CALCIUM SULFOALUMINATE		12004-14-7	1-10%	Xi;R41.
HIGH ALUMINA CEMENT			1-10%	Xi;R41,R36/37.
PORTLAND CEMENT		65997-15-1	10-30%	Xi;R37/38,R41. R43.
SILICA SAND	238-878-4	14808-60-7	30-60%	-

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Risk of serious damage to eyes.

#### INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

#### INGESTION

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

#### SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Water. Foam.

#### SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT****UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
HIGH ALUMINA CEMENT		10 mg/m <sup>3</sup>		
PORTLAND CEMENT	WEL	10 mg/m <sup>3</sup>		
SILICA SAND	WEL	0.3 mg/m <sup>3</sup>		

**WEL = Workplace Exposure Limit.****PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT****APPEARANCE** Powder, dust**RELATIVE DENSITY** 1.6-2.0 @ 20°C**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL** The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).**15 REGULATORY INFORMATION****LABELLING**

Irritant

**CONTAINS** PORTLAND CEMENT**RISK PHRASES**

R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.

**SAFETY PHRASES**

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37/39	Wear suitable gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT****ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 02/08/2010**REV. NO./REPL. SDS GENERATED** 8**RISK PHRASES IN FULL**

R36/37	Irritating to eyes and respiratory system.
R37/38	Irritating to respiratory system and skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



## SAFETY DATA SHEET

### ULTRASCAPE FLOWPOINT CHARCOAL

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

<b>PRODUCT NAME</b>	ULTRASCAPE FLOWPOINT CHARCOAL
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

#### 2 HAZARDS IDENTIFICATION

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

**CLASSIFICATION (1999/45)** Xi;R37/38, R41. R43.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
CALCIUM CARBONATE GRANULES			10-30%	-
CALCIUM SULFOALUMINATE		12004-14-7	1-10%	Xi;R41.
HIGH ALUMINA CEMENT			1-10%	Xi;R41,R36/37.
PORTLAND CEMENT		65997-15-1	10-30%	Xi;R37/38,R41. R43.
SILICA SAND	238-878-4	14808-60-7	30-60%	-

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Risk of serious damage to eyes.

##### INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

##### INGESTION

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

##### SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

##### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Water. Foam.

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT CHARCOAL****SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CALCIUM CARBONATE GRANULES	WEL		4 mg/m <sup>3</sup>			
HIGH ALUMINA CEMENT			10 mg/m <sup>3</sup>			
PORTLAND CEMENT	WEL		10 mg/m <sup>3</sup>			
SILICA SAND	WEL		0.3 mg/m <sup>3</sup>			

**WEL = Workplace Exposure Limit.****PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT CHARCOAL****HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE** Powder, dust  
**RELATIVE DENSITY** 1.6-2.0 @ 20°C

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

**GENERAL** The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**CONTAINS** PORTLAND CEMENT

**RISK PHRASES**

R37/38 Irritating to respiratory system and skin.  
 R41 Risk of serious damage to eyes.  
 R43 May cause sensitisation by skin contact.

**SAFETY PHRASES**

S24/25 Avoid contact with skin and eyes.  
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

REVISION DATE: 02/08/2010

**ULTRASCAPE FLOWPOINT CHARCOAL**

S37/39	Wear suitable gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 02/08/2010**REV. NO./REPL. SDS GENERATED** 6**RISK PHRASES IN FULL**

R36/37	Irritating to eyes and respiratory system.
R37/38	Irritating to respiratory system and skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244